

**DMC
SONORA
CHAMBERS**

dmc 
SONORA

**SOUNDPROOF
CHAMBERS**

**SEMI
ANECHOIC
CHAMBER**






www.dmcrf.com

////////////////////
Ultra-Premium Quality
Best Performance
35+ Years Experience

INSULATION LEVEL (TRANSMISSION LOSS) / dB										
		Hz	63	125	250	500	1000	2000	4000	8000
Guaranteed Insulation Value	X	(20)	30	36	40	49	53	55	54	
	S	(28)	35	41	45	51	55	57	56	
	H	(32)	40	46	50	56	60	62	61	
Actual Shielding Amount	X	32.6	49.4	62.4	74.5	77.8	83.1	81.5	81.5	
	S	33.4	50.3	59.0	63.1	64.9	68.6	78.0	84.2	
	H	41.9	50.8	60.1	71.3	75.1	77.3	79.9	86.0	

MODELS	WEDGES	INWARD (MM)	OUTWARD (MM)
DMC-ASACWOF-27312800	HV02W	W2000 × L2400 × H2450	W2700 × L3100 × H2800
DMC-ASACWF-27312900	HV02W	W2000 × L2400 × H2450	W2700 × L3100 × H2900
DMC-ASACWOF-31372800	HV02W	W2400 × L3000 × H2450	W3100 × L3700 × H2800
DMC-ASACWF-31372900	HV02W	W2400 × L3000 × H2450	W3100 × L3700 × H2900
DMC-ASACWOF-37432800	HV02W	W3000 × L3600 × H2450	W3700 × L4300 × H2800
DMC-ASACWF-37432900	HV02W	W3000 × L3600 × H2450	W3700 × L4300 × H2900
DMC-ASACWOF-27312800	T-250	W2000 × L2400 × H2450	W2700 × L3100 × H2800
DMC-ASACWF-27312900	T-250	W2000 × L2400 × H2450	W2700 × L3100 × H2900
DMC-ASACWOF-31372800	T-250	W2400 × L3000 × H2450	W3100 × L3700 × H2800
DMC-ASACWF-31372900	T-250	W2400 × L3000 × H2450	W3100 × L3700 × H2900
DMC-ASACWOF-37432800	T-250	W3000 × L3600 × H2450	W3700 × L4300 × H2800
DMC-ASACWF-37432900	T-250	W3000 × L3600 × H2450	W3700 × L4300 × H2900
DMC-ASACWOF-32363050	T-500	W2000 × L2400 × H2450	W3200 × L3600 × H3050
DMC-ASACWF-32363150	T-500	W2000 × L2400 × H2450	W3200 × L3600 × H3150
DMC-ASACWOF-36423050	T-500	W2400 × L3000 × H2450	W3600 × L4200 × H3050
DMC-ASACWF-36423150	T-500	W2400 × L3000 × H2450	W3600 × L4200 × H3150
DMC-ASACWOF-42483050	T-500	W3000 × L3600 × H2450	W4200 × L4800 × H3050
DMC-ASACWF-42483150	T-500	W3000 × L3600 × H2450	W4200 × L4800 × H3150

For custom size please contact us

SOUND ABSORPTION WEDGE SIZE	T-250	HV02W	T-500
			

SPECIFICATION

Single swing sound insulation door: Inner wall sound absorption layer
Floor panel + reflection plate (Excluding cases without floor)
Vibration isolation layer
Utility pipe diameter 65 + inside and outside sound insulation cover
Microphone hanging hook
Air supply diffraction silencer
Exhaust diffraction silencer
Complete documents (drawings, specifications, etc.)
Light bulb type LED lighting
Outlet 100V-3P-2 ports
Indicator light 10W "In use" text
Sirocco fan + flexible silencer
Switch box, distribution board
2 Next side wiring work

OPTIONS

Air conditioning equipment
Monitor
Signal light
Sound Absorption BNC Shelf
Intercom
Earthquake resistant design
Gas Alarm
Fire Alarm etc.



Diamond Microwave Chambers Ltd
15 Fitzgerald Rd, Suite 200
Ottawa, ON K2H 9G1
Canada
Ph.+1(613) 915 5533
sales@dmcrf.com